



Technical

Specifications

SN 400

PARAMETERS	TEST METHOD	UNITS	GUARANTEED	TYPICAL
Kinematic viscosity at 100 °C	GOST 33-2016	cSt	9,00 -10,50	9,2
Kinematic viscosity at 40 °C	GOST 33-2016	cSt	-	79,25
Viscosity index	GOST 25371-2018	-	Min 90	90
Sulfur content	ASTM D 4294-03	%	Max 0,3	0,1
Water	GOST 2477-2914	%	Max traces	traces
Density at 15°C	GOST R 51069-97	kg/m3	Max 903	885
Pour point	GOST 20287-91 (B)	° C	Max -9	-15
Evaporation loss NOACK	ASTM D 5800-03a	%	Max 8	6
Color	GOST 20284-74		Max 2,5	1,5
Flash point	GOST 4333-2014	° C	Min 225	229
Appearance	Visual	-	Clear & Bright	Clear & Bright

Handling Health & Safety :

Lubricants consisting of highly refined mineral oils with specification additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.

İNOVATİF MAKİNA PETROL LOJİSTİK İTHALAT
İHRACAT SANAYİ VE TİCARET LİMİTED ŞİRKETİ
KÜME EVLERİ TRAK DEPOLARI NO : 444 İÇ KAP / NO 6 MERKEZ / EDİRNE
V.D : KIRKPINAR VKN : 663 094 0035



ASTM INTERNATIONAL