



Technical Specifications

60N

PARAMETERS	TEST METHOD	UNITS	GUARANTEED	TYPICAL
Appearance	ASTMD4176	-	C&B	C&B
Color ASTM	ASTMD1500	-	Max 0,5	L0,5
Kinematic viscosity at 40 °C	ASTMD445	mm ² /s	7,0 – 8,5	7,74
Kinematic viscosity at 100 °C	ASTMD445	mm ² /s	-	2.14
Viscosity index	ASTMD2270	-	Min 60	66
Pour point	ASTMD6749	°C	Max -15	-16
Flash point	ASTMD92(COC)	°C	Min 145	158
Sulfur	ASTMD5453	wppm	Max 10	4,0
TAN	ASTMD664	mgKOH/g	Max 0,01	0,004

Handling Health & Safety :

Lubricants consisting of highly refined mineral oils with specification additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding can contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.

İNOVATİF MAKİNA PETROL LOJİSTİK İTHALAT
İHRACAT SANAYİ VE TİCARET LİMİTED ŞİRKETİ
KÜME EVLERİ TRAK DEPOLARI NO : 444 İÇ KAP / NO 6 MERKEZ / EDİRNE
V.D : KIRKPINAR VKN : 663 094 0035



ASTM INTERNATIONAL