



Technical

Specifications

8 cSt

PARAMETERS	TEST METHOD	UNITS	GUARANTEED	TYPICAL
Appearance	Visual	-	Clear colorless or light yellow liquid	Clear light yellow liquid
Color ASTM	ASTM D 1500	-	Max 0,5	0,5
Kinematic viscosity at 40 °C	ASTM D 445	mm ² /s	-	46,4
Kinematic viscosity at 100 °C	ASTM D 445	mm ² /s	7,5 - 7,8	7,7
Viscosity index	ASTM D 2270	-	Min 125	132
Pour point	ASTM D 97	°C	Max -25	-35
Flash point open cup	ASTM D 92	°C	Min 230	238
Sulfur	ASTM D 6481	ppm	Max 10	L3
NOACK	ASTM D 5800	% mass.	Max 8,0	5,7
Density at 20°C	ASTM D 4052	kg/m ³	-	833

Handling Health & Safety :

Lubricants consisting of highly refined mineral oils with specification additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding can contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.

İNOVATİF MAKİNA PETROL LOJİSTİK İTHALAT
İHRACAT SANAYİ VE TİCARET LİMİTED ŞİRKETİ
KÜME EVLERİ TRAK DEPOLARI NO : 444 İÇ KAP / NO 6 MERKEZ / EDİRNE
V.D : KIRKPINAR VKN : 663 094 0035



ASTM INTERNATIONAL