



Technical

Specifications

600N

PARAMETERS	UNITS	GUARANTEED	TYPICAL
Appearance	-	C&B	C&B
Color ASTM	-	Max 0,5	L0,5
Kinematic viscosity at 40 °C	mm ² /s	-	107,00
Kinematic viscosity at 100 °C	mm ² /s	12,0 - 12,9	12,03
Viscosity index	-	Min 95	102
Pour point	°C	Max -12	-18
Flash point	°C	Min 246	276
Sulfur	wtppm	Max 10	4
Aromatics	%	Max 1.0	0.0
TAN	mgKOH/g	Max 0,01	0,004

Handling Health & Safety :

Lubricants consisting of highly refined mineral oils with specification additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.

İNOVATİF MAKİNA PETROL LOJİSTİK İTHALAT
İHRACAT SANAYİ VE TİCARET LİMİTED ŞİRKETİ
KÜME EVLERİ TRAK DEPOLARI NO : 444 İÇ KAP / NO 6 MERKEZ / EDİRNE
V.D : KIRKPINAR VKN : 663 094 0035



ASTM INTERNATIONAL