



# Technical

# Specifications

## SN 80

PARAMETERS	TEST METHOD	UNITS	GUARANTEED	TYPICAL
ASTM Color	ASTM D 1500	-	Max 0,5	L0,5
Density at 15°C	ASTM D 4052	kg/l	Max 0,860	0,849
Kinematic viscosity at 40 °C	ASTM D 445	mm <sup>2</sup> /s	14,0 – 17,0	15,2
Viscosity index	ASTM D 2270	-	Min 97	105
Pour point	ASTM D 97	°C	Max -6	-9
Flash point COC	ASTM D 92	°C	Min 180	194
Neutralization Number	IP 1A	mgKOH/g	Max 0,03	< 0,01

### Handling Health & Safety :

Lubricants consisting of highly refined mineral oils with specification additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding can contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.

İNOVATİF MAKİNA PETROL LOJİSTİK İTHALAT  
İHRACAT SANAYİ VE TİCARET LİMİTED ŞİRKETİ  
KÜME EVLERİ TRAK DEPOLARI NO : 444 İÇ KAP / NO:6 MERKEZ / EDİRNE  
V.D. : KIRKPINAR VKN : 663 094 0035



ASTM INTERNATIONAL